

Primer & Filler Black

Bardahl Primer & Filler is a very strong and fast drying filler. This product fills, repairs and covers small holes and imperfections and perfects repaired surfaces.

Bardahl Primer & Filler can also be used as a primer to give different surfaces a durable protective layer. Provides the body with a smooth layer, which can also be sanded and repainted.

Where to use

This product can be used with all forms of conventional metal surfaces and most synthetic lacquers and coatings.

Where not to use

This product should not be used on flexible plastic surfaces.

Advantages

- Special formulation to fill and smooth surfaces.
- Provides a smooth matte finish that is easy to sand.
- Excellent adhesion to metals and to old paint layers.
- Compatible with the most commonly used car paints.
- Very flexible
- Prevents waste of material.
- Fills quickly.
- Dries quickly.
- Available in black, grey and white

Analytical data

Test	Results
Appearance	A smooth viscous mobile liquid
Viscosity	700 – 1,200 cPs, nominaal bij 20°C
Density	1.105 – 1.145 nominaal bij 20°C
Solids % w/w	79.2 +/- 1%
Carrier % w/w	20.8 +/- 1%
Volatile Organic Content	2004/42/IIB(e) (840) 653
Flammability	Extremely flammable, flash point -20°C.
Drying time	Approximately 20 minutes at 20°C
Optimal user damp.	Between 10°C and 25°C



Manual

Shake the can well before use. For best results, clean the surface well with Bardahl Bodysol. Use the primer & filler at room temperature, spray it on the surface at a distance of 30-40cm. Let it dry for 20 minutes. If desired, the surface can be sanded.

After use, turn the can over and spray until only gas escapes. This cleans the spray head.

Black

Article number 65305

Contents 500 ml