

Intercoating ML (SPRAY)

Bardahl Intercoating ML is an anti-corrosion product, specially developed for the protection of hollow spaces in car bodies such as doors and box beams. **Bardahl Intercoating ML** is composed of basic raw materials with strong penetrating properties. As a result, a durable anti-rust treatment of also hard-to-reach body parts such as door frames and welds is possible without problems. After application, a dry, non-sticking film with a layer thickness of approx. 20-40 microns is created. This layer is amber and transparent. Due to the excellent temperature resistance, corrosion-resistant treatment of the trunk lid and bonnet is also possible. In addition to this specific ML treatment, the product can also be used to protect metal parts, metal surfaces and tools during storage and transport.

Processing

Bardahl Intercoating ML in packaging, is a universal under screw vial for processing with ML spray guns. 1 liter

Removal

Bardahl Intercoating ML can be easily removed with turpentine.

Analysis data

Test			Results
Class - Coatings	Method	Unit	Intercoating ML
Colour			amber bruin
Solids	DIN 53216	%	49-54
Flashpunt	ASTM D 1320-67	°C	>39
Viscosity (20°C)	DIN-cup nr. 4	cP	30 +/- 5 sec
Density (20°C)	DIN 51757	Kg/l	0.86 +/- 0.02

Article number 63105
Content 500 ml (spray)