

Engine Cleaner / Degreaser BIO

Bardahl Engine Cleaner/ Degreaser is composed of high-quality solvents and selected surfactants. Because the emulsifier wears off within 15 minutes after rinsing with water, the rinsing water disintegrates into oil and a water phase.

Bardahl Engine Cleaner/ Degreaser is applied to the objects to be cleaned by spraying or using a brush or brush. For cleaning smaller workpieces, a dipping procedure can also be used. This highly concentrated degreaser dissolves oil, grease, and tar quickly and effortlessly.

Applications

- For cleaning engines, gearboxes, cards, axles, etc. Apply with a syringe or brush and then spray with water.
- For removing the paraffin layer of new cars. Apply with brushing rags or brush. When the paraffin layer is dissolved, rinse with water and dry with a chamois.
- For removing oil and grease from floors. Sprinkle the bottom and distribute with a broom or brush. Then spray with water and drain.
- For the removal of tar and storage tanks, tankers, and road construction machines.

Manual

The degreaser needs a few minutes to penetrate the dirt layer. After 3 – 5 minutes of soaking, the dirt can be removed with running water or with water and brush.

Analytical data

Test			Results
Degreaser - Class	Method	Unit	Engine Cleaner / Degreaser
Density 15°C		g/ml	0,78
Colour			blank
Aromatics % m/m	SMS 2728	% m/m	0,02
Benzene quality mg/kg		mg/kg	5 (Gas Chrom.)
Bromine index mgBr/100gr	ASTM D1492	mgBr/100gr	200
Flashpoint °C		°C	42 (Abel)

Biodegradable

Bardahl Engine Cleaner/ Degreaser is biodegradable. The biodegradability, measured according to the CEC L-33-T-82 test, is 90%.



Article number 61204
Contents 400 ml

Article number 61255
Contents 5 liter

Article number 61282
Contents 25 liter

Article number 61286
Contents 60 liter

Article number 61292
Contents 200 liter

Information regarding detergents can be found on the SDS of this product.